

## Floor Sealer

### FC 1150

### Description

A floor sealer designed to create a strong, uniform base on worn VCT, linoleum, and tile. Enhances finish adhesion and improves appearance while extending the life of the floor system. Ideal for preparing older floors for a smooth, professional finish.

### Where To Use

For low maintenance areas such as:

- Schools and offices
- Hospitals and institutions
- Supermarkets and shopping centers

### Features

- Seals and finishes most porous stone
- Terrazzo, and concrete floors
- Extremely durable and economical

### Directions

- **1** **Wear safety glasses & gloves**  
*Usar gafas de seguridad y guantes*
- **2** **Apply 1-2 coats evenly with clean mop**  
*Aplique uniformemente 1-2 capas con una mopa de limpieza*
- **3** **Allow to dry 30-45 minutes between coats**  
*Deje secar 30-45 minutos entre una capa y otra*
- **4** **Completely dry before applying next coat**  
*Seque completamente antes de aplicar la capa siguiente*
- **5** **Apply floor finish**  
*Aplique el acabado para pisos*

### Specification Data

Color .....	White
Fragrance .....	Characteristic
pH Range .....	8.0 - 8.5
Dilution .....	RTU
Density .....	8.67

### Packaging

- 4 / 1 Gallon
- 2 / 2.5 Gallont
- 5 Gallon
- 55 Gallon

