

## Zinc-Free High Traffic Floor Finish

### FC 1235

### Description

This environmentally responsible floor finish delivers a hard, durable coating built to withstand high-traffic areas while maintaining a long-lasting, professional appearance. Green Seal and UL ECOLOGO<sup>®</sup> certified.

### Where To Use

For low maintenance areas in:

- Schools and offices
- Shopping centers and retail
- Hospitals and medical centers

### Features

- High off the mop gloss
- Fast drying
- Low odor

### Directions

- 1** Wear safety glasses & gloves  
*Usar gafas de seguridad y guantes*
- 2** Apply 3-5 coats evenly with a clean finish mop  
*Aplique 3 - 5 capas de manera uniforme con un trapeador de acabado limpio*
- 3** Allow to dry 30-45 minutes between coats  
*Deje secar 30-45 minutos entre una capa y otra*
- 4** Completely dry before applying next coat  
*Seque completamente antes de aplicar la capa siguiente*
- 5** Let dry completely before allowing traffic  
*Dejar secar completamente antes de permitir el tránsito*

### Specification Data

Color .....	White
Fragrance .....	Mild Pine
pH Range .....	8.0 - 8.5
Dilution .....	RTU
Density .....	8.59

### Packaging

- 4 / 1 Gallon
- 2 / 2.5 Gallon
- 5 Gallon
- 55 Gallon

### Certifications

