

Hardcoat

FC 1630

Description

A durable sealer designed to protect concrete, terrazzo, and other stone surfaces. Offers excellent resistance to chemicals, including grease, oil, and gasoline. Ideal for long-lasting performance in demanding environments.

Where To Use

For sealing and protecting:

- Concrete and brick
- Slate and quarry tile
- Unglazed ceramic tile

Features

- Low odor, quick drying
- Durable, resists scuffs and marks
- Non-yellowing, non-flammable

Directions

-  **1** **Wear safety glasses & gloves**
Usar gafas de seguridad y guantes
-  **2** **Apply 1-2 coats evenly with a clean finish mop**
Aplique 1 - 2 capas de manera uniforme con un trapeador de acabado limpio
-  **3** **Wait 30-45 minutes between coats**
Espera de 30 - 45 minutos entre capas
-  **4** **Completely dry before applying next coat**
Seque completamente antes de aplicar la capa siguiente
-  **5** **Allow final coat to dry for 6 - 8 hours**
Permita que la capa final se seque durante 6 - 8 horas

Specification Data

| | |
|-----------------|----------------|
| Color | White |
| Fragrance | Characteristic |
| pH Range | 8.0 - 8.5 |
| Dilution | RTU |
| Density | 8.59 |

Packaging

- 5 Gallon
- 55 Gallon

