

Issue Date: 08-Aug-2011

Revision/Review Date: 18-Jul-2024

Version 1.4

1. IDENTIFICATION

Product Identifier

Product Name Maxim Commercial Floor Stripper

Other Means of Identification

Product Code 110400

Recommended use of the Chemical and Restrictions on Use

Recommended Use Floor stripper concentrate. For industrial and institutional use.

Details of the Supplier of the Safety Data Sheet

Midlab, Inc.
140 Private Brand Way
Athens, TN 37303

Emergency Telephone Number

Company Phone Number Phone: 1-423-337-3180
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Colorless

Physical State Liquid

Odor Citrus

Classification

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 1
Serious eye damage/eye irritation	Category 1
Skin Sensitization	Category 1
Corrosive to Metals	Category 1

Signal Word

Danger



Hazard Statements

Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
May be corrosive to metals.

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Do not breathe dusts or mists.
Wear protective gloves/protective clothing/eye protection/face protection.
Contaminated clothing should not be allowed out of the workplace.
Keep only in original packaging.

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if symptoms persist.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor.

SPECIFIC TREATMENT: Remove from exposure and treat symptoms.

IN CASE OF SPILL: Absorb spillage to prevent material-damage.

Precautionary Statements - Storage

Store locked up.

Store in a corrosion resistant container with a resistant inner liner.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant.

Other Hazards

May be harmful to aquatic life with long lasting effects.

Unknown Acute Toxicity

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Butoxyethanol	111-76-2	10-30
Ethanolamine	141-43-5	5-10
Potassium Hydroxide	1310-58-3	1-5
Fragrance	Proprietary	0.1-1.0

**If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret. **

4. FIRST-AID MEASURES

First Aid Measures

Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Seek immediate medical attention/advice. If possible, continue to flush eyes with running water until medical attention is received.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Take off contaminated clothing. Wash contaminated clothing before reuse. Seek medical attention of burns or rash occurs.
Inhalation	Remove to fresh air. Call a physician or poison control center immediately.
Ingestion	Rinse mouth. Drink plenty of water. Seek medical attention immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Most Important Symptoms and Effects

Symptoms	Corrosive to eyes. Corrosive and irritating to upper respiratory tract. Prolonged contact may even cause severe skin irritation or mild burn.
-----------------	---

Indication of any Immediate Medical Attention and Special Treatment Needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray (fog). Carbon dioxide (CO₂). Dry chemical. Foam.

Unsuitable Extinguishing Media

Not determined.

Specific Hazards Arising from the Chemical

None known.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions Use personal protective equipment as required.

Environmental Precautions Avoid release to the environment.

Methods and Material for Containment and Cleaning Up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Safety glasses and gloves should be worn when cleaning up spillage. Collect in a clean, dry waste container for disposal. Dispose of in accordance with federal, state and local regulations. Dilute remaining residue with water.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Advice on Safe Handling Wash thoroughly after handling. Use personal protection recommended in Section 8. Do not eat, drink, or smoke when using this product. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Avoid contact with skin and eyes.

Conditions for Safe Storage, including any Incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool, and well-ventilated place. Keep locked up and out of reach of children. Keep from freezing.

Incompatible Materials Acids. Oxidizing agents. Bleach.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S*S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
Ethanolamine 141-43-5	STEL: 6 ppm TWA: 3 ppm	TWA: 3 ppm TWA: 6 mg/m ³ (vacated) TWA: 3 ppm (vacated) TWA 8 mg/m ³ (vacated) STEL: 6 ppm (vacated) STEL: 15mg/m ³	IDLH: 30 ppm TWA: 3 ppm TWA: 8 mg/m ³ STEL: 6 ppm STEL: 15mg/m ³
Potassium Hydroxide 1310-58-3	Ceiling: 2 mg/m ³	(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³

Appropriate Engineering Controls

Engineering Controls Ensure adequate ventilation, especially in confined areas. Good general room ventilation should be adequate under normal use conditions.

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection Splash goggles or safety glasses.

Skin and Body Protection	Rubber, Nitrile, PVC, or other chemically resistant skin protection to prevent contact.
Respiratory Protection	Ensure adequate ventilation, especially in confined areas.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	Liquid	Odor	Citrus
Appearance	Clear	Odor Threshold	Not determined
Color	Colorless		
<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>	
pH	13.0-14.0		
Melting Point/Freezing Point	~ 0 °C / ~32 °F		
Boiling Point/Boiling Range	~ 100 °C / ~212 °F		
Flash Point	Not applicable		
Evaporation Rate	Not determined		
Flammability (Solid, Gas)	n/a-liquid		
Upper Flammability Limits	Not determined		
Lower Flammability Limit	Not determined		
Vapor Pressure	Not determined		
Vapor Density	Not determined		
Specific Gravity	1.03		
Water Solubility	Completely soluble	@ 25 °C (77 °F)	
Solubility in other solvents	Not determined		
Partition Coefficient	Not determined		
Auto-ignition Temperature	Not determined		
Decomposition Temperature	Not determined		
Kinematic Viscosity	Not determined		
Dynamic Viscosity	Not determined		
Explosive Properties	Not determined		
Oxidizing Properties	Not determined		

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to Avoid

Keep out of reach of children. Keep from freezing.

Incompatible Materials

Acids. Oxidizing agents. Bleach.

Hazardous Decomposition Products

When exposed to fire, produces normal products of combustion.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Product Information

Eye Contact Causes severe eye damage.

Skin Contact	Causes severe skin burns. May be harmful in contact with skin.
Inhalation	Harmful if inhaled.
Ingestion	Harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Butoxyethanol 111-76-2	= 470 mg/kg (Rat)	= 2270 mg/kg (Rat) = 220 mg/kg (Rabbit)	= 2.21 mg/L (Rat) 4 h = 450 ppm (Rat) 4 h
Ethanolamine 141-43-5	= 1720 mg/kg (Rat)	= 1 mL/kg (Rabbit) = 1025 mg/kg (Rabbit)	-
Potassium Hydroxide 1310-58-3	214 mg/kg (Rat)	-	-

Information on Physical, Chemical and Toxicological Effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-Term Exposure

Carcinogenicity Not classifiable as a human carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Butoxyethanol 111-76-2	A3	Group 3		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 3 IARC components are "not classifiable as human carcinogens"

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

Chronic toxicity Chronic exposure may cause liver, kidney and/or blood disorders.

Numerical Measures of Toxicity

Not determined

Unknown Acute Toxicity None known.

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Harmful to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Butoxyethanol 111-76-2	-	1490: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 2950: 96 h <i>Lepomis macrochirus</i> mg/L LC50	-	1698 - 1940: 24 h <i>Daphnia magna</i> mg/L EC50 1000: 48 h <i>Daphnia magna</i> mg/L EC50
Ethanolamine 141-43-5	15: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	227: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 3684: 96 h <i>Brachydanio rerio</i> mg/L LC50 static 300 - 1000: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 114 - 196: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static 200: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 flow-through	-	65: 48 h <i>Daphnia magna</i> mg/L EC50
Potassium Hydroxide 1310-58-3	-	80: 96h <i>Gambusia affinis</i> mg/L LC50 static	-	-

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Butoxyethanol 111-76-2	0.81
Ethanolamine 141-43-5	-1.91
Potassium Hydroxide 1310-58-3	0.83

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national, and local laws and regulations.

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT UN/ID No UN1760, Corrosive Liquid, NOS (Containing Ethanolamine and Potassium Hydroxide), 8, PG II

IATA

IMDG Marine Pollutant This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

Canada – Domestic Substances List (DSL) All ingredients are listed or exempt.
 TSCA (Toxic Substances Control Act) All ingredients are listed or exempt.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

CERCLA

This material, as supplied, contains one or more substance regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substance RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Potassium Hydroxide 1310-58-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard Yes
Reactive Hazard Yes

SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Butoxyethanol	111-76-2	10-30	1.0

US State Regulations

California Proposition 65

This product does not contain any chemical known to the State of California to cause cancer.

U.S. State Right-to-Know Regulations

Chemical Name	State List
Butoxyethanol 111-76-2	MA, NJ, PA
Ethanolamine 141-43-5	MA, NJ, PA
Potassium Hydroxide 1310-58-3	MA, NJ, PA

AZ – Arizona Ambient Air Quality Guidelines
 CT – Connecticut Hazardous Air Pollutants
 CA – California Director’s List of Hazardous Substances
 CAP65 – California Prop 65
 FL – Florida Substances List
 ID – Idaho Non-Carcinogen Toxic Air Pollutants

IL – Illinois Toxic Air Contaminant- Carcinogenic
 MA – Massachusetts Right to Know List
 MN – Minnesota Hazardous Substances List
 NJ – New Jersey Right to Know List
 PA – Pennsylvania Right to Know List
 RI – Rhode Island Hazardous Substances List

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	Not determined	Not determined	Not determined	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	3	0	0	Glasses, gloves

Issue Date: 08-Aug-2011
Revision/Review Date: 18-Jul-2024
Revision Note: Version 1.4 Updated Sections 2 & 15.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Keep Out of Reach of Children. For Industrial and Institutional Use Only.

*Denotes changes from last version.

End of Safety Data Sheet